




 **FIXCERA**



TILE ADHESIVES

—
TECHNICAL DATA SHEET





CONSISTENTLY OUTSTANDING

FIXCERA T1T

Polymer modified adhesive for fixing new tiles or natural stones over existing tiles or stones. Also suitable for fixing glass mosaics, vitrified tiles, ceramic tiles, terrazzo and natural stones over various substrates in interior and exterior areas over floors and walls.

Suitable for use in wet areas.

FEATURES AT A GLANCE

- Specialized for tile over tile application
- Multipurpose and suitable for all tile types
- Single component, easy to use
- For use in interior and exterior areas
- Excellent adhesion over various substrates
- Shock resistant
- Complies with EN C2TE classification
- Complies with IS 15477:2019 - Type 3T standard
- Complies with ANSI A118.4TE specifications
- Available in sturdy 20kg bags

TECHNICAL DATA SHEET



TILE ON TILE ADHESIVE

COMPLIANCE AND FEATURES



PROUDLY MADE IN INDIA

RECOMMENDATION

Best suited for tile on tile application. Also ideal for installation of glass mosaics, vitrified tiles, ceramic tiles, terrazzo and natural stones over a variety of substrates. Suitable for wet areas and for wet-on-wet application.

CONSISTENTLY OUTSTANDING

Tile Adhesives | Tile Joints | Waterproofing | Admixtures

www.fixcera.com
support@fixcera.com



CONSISTENTLY OUTSTANDING

ECO FRIENDLINESS

This product can be recycled as an inert mineral substance once cured

This product contains negligible Volatile Organic Compounds (VOCs)

This product when used instead of the traditional thick-bed method reduces material transportation and total cement consumption, thus significantly reducing harmful CO₂ emissions

TECHNICAL DATA SHEET



PACKAGING

- 20kg bags

COVERAGE

- 5 - 5.5 m²/ 20kg bag

COLORS

- Grey and White

MIXING RATIO

- Approx. 5.5L/ 20kg bag

BEST SUITED SUBSTRATES

- Concrete
- Concrete masonry
- Cement-based screeds
- Cement plaster
- Cement terrazzo
- Brick masonry
- Waterproofing products
- Existing ceramic tiles
- Existing vitrified tiles
- Existing natural stones
- Existing glass mosaics

TECHNICAL DATA

PARAMETER	VALUE	REFERENCE STANDARD
Shelf Life	12 months from manufacturing	
Packaging	20kg bag	
Colors	Grey and White	
Coverage/mm Thickness	1.2kg/m ²	
Pot Life at 25°C	Approx. 4 hours	
Water Demand	5.5L/ 20kg bag	
Foot Traffic at 25°C	24 hours	
Open Time	30 minutes	IS 15477:2019 Annex C (Clause 5.3)
Adjustment Time	30 minutes	IS 15477:2019 Annex D (Clause 5.4)
Slip	0.1 - 0.3 mm	IS 15477:2019 Annex E (Clause 5.5)
Open Time Tensile Adhesion (30 minutes at 28 days)	125 - 140 psi	ANSI A118.4 Clause 5.3
Shear Strength at 28 days (Porcelain Mosaic Tile)	250 - 280 psi	ANSI A118.4 Clause 7.2.5
Durability: Tensile Adhesion After Water Immersion	1.20 - 1.50 N/mm ²	EN 1348 Clause 8.3
Durability: Tensile Adhesion After Heat Aging	1.00 - 1.20 N/mm ²	EN 1348 Clause 8.4
Durability: Tensile Adhesion After Freeze-Thaw	1.20 - 1.50 N/mm ²	EN 1348 Clause 8.5
Transverse Deformation	NA	ISO 13007-2 Clause 4.5

INSTRUCTIONS FOR USE

SUBSTRATE PREPARATION

- All suitable substrates must be stable in accordance with IS 1443
- All suitable substrates must be completely cured, rigid, and leveled within a variation of no more than 3mm in 3m
- All suitable substrate must be free from debonding/ demolding agents
- All suitable substrates must be free from any damp risings
- All suitable substrates must be free of all dirt, grease, sealers, fiber mesh or any loose particles
- Dampen absorbent cement-based surfaces and sweep off excess water

ADHESIVE MORTAR PREPARATION

- Pour clean potable water into a mixing bucket
- Add FixCera Tile Adhesive to the water
- Use about 5.5L of water per 20kg bag of Adhesive
- Mix well using a low-speed paddle drill mixer
- Allow the mixture to rest for 5 minutes
- Mix again and use

INSTRUCTIONS FOR USE

APPLICATION OF THE MORTAR

- Use the straight edge of a trowel to apply a thin coat of the adhesive onto the substrate
- Comb additional mortar on the surface using a notched trowel held at an angle of 45 from the leveled surface
- Place and then press the tile firmly into place with a slight twisting motion
- Back-buttering is necessary for all large format tiles
- Periodically check tiles for complete wetting by the adhesive mortar
- If the adhesive mortar has 'skinned' and results in incomplete wetting of the tile surface, discard the adhesive and replace it with fresh mortar
- Create elastic expansion joints as per requirement
- For highly absorbent natural stones, use an appropriate FixCera Sealer prior to installation
- Remove any surplus adhesive from the tile while adhesive is still fresh

STORAGE

- Store the adhesive powder in a cool and dry place
- Keep away from sunlight



CONSISTENTLY OUTSTANDING

TECHNICAL DATA SHEET

INSTRUCTIONS FOR USE

GROUTING

- Grouting should be commenced after at least 24-48 hours of curing time

HEALTH PRECAUTIONS

- This product is limited to professional use only
- This product contains Portland Cement and Silica
- Wear suitable protective clothing, gloves and eye/ face protection
- Avoid contact with eyes and prolonged contact with skin
- Kindly refer to the Safety Data Sheet for further information.

SAM/FIXCERA/TA/T1T/TDS - REV 00 - 10/21

Disclaimer

The information and any recommendation, technical or otherwise, contained within this document are presented in good faith and believed to be correct as of the date prepared. Recipients of this information and recommendations must make their own determination as to its suitability for their purpose. In no event shall Samrat Coatings and Adhesives Pvt Ltd assume liability for damages or losses of any kind or nature that result from the use of or reliance upon this information and recommendations. Samrat Coatings and Adhesives Pvt Ltd expressly disclaims any representations and warranties of any kind, whether express or implied, as to the accuracy, completeness, non-infringement, merchant-ability and/ or fitness for a particular purpose (even if Samrat Coatings and Adhesives is aware of such purpose) with respect to any information and recommendations provided. Reference to any trade names used by other companies is neither a recommendation nor an endorsement of the corresponding product, and does not imply that similar products could not be used. Samrat Coatings and Adhesives Pvt Ltd reserves the right to make any changes to the information and/ or recommendations at any time, without prior or subsequent notice.

CONSISTENTLY OUTSTANDING

Tile Adhesives | Tile Joints | Waterproofing | Admixtures

www.fixcera.com
support@fixcera.com